



Rotation reference: BTD...I=Rotation left
 BTD...D=Rotation right
 Min 600 rpm

Part n°	R1	R2	Max. Press. (bar)	Max. Peak press.	R.P.M.	cm ³ / rev	A	B
BTD111D01	3/8" BSP	3/8" BSP	250	300	6000	1,1	75	33
BTD116D01	3/8" BSP	3/8" BSP	250	300	6000	1,6	78	35
BTD118D01	3/8" BSP	3/8" BSP	250	300	6000	1,8	78,5	35,5
BTD127D01	3/8" BSP	3/8" BSP	250	300	6000	2,7	81	37
→ BTD132D01	3/8" BSP	3/8" BSP	250	300	5000	3,2	83	38
BTD137D01	3/8" BSP	3/8" BSP	250	300	4500	3,7	85	39
BTD148D01	3/8" BSP	3/8" BSP	200	250	4000	4,8	89	41
BTD158D01	1/2" BSP	3/8" BSP	200	250	3500	5,8	93	43

The information gathered in this technical documentation (Catalogue) has an informative character and can be modified without previous notice. DM will not accept any type of responsibility resulting from an inappropriate use of the product, except the ones related to manufacturing defects.

Gear Pumps

Gear pumps Group I Right

Eur.cover/Threaded fl./Conical 1:8 Gr.I

Page: 2/2

Part nº	R1	R2	Max. Press. (bar)	Max. Peak press.	R.P.M.	cm ³ / rev	A	B
BTD163D01	1/2" BSP	3/8" BSP	200	250	2900	6,3	97	45
BTD180D01	1/2" BSP	3/8" BSP	200	250	2100	8	101	47

*R.P.M.=Máx. speed

R1 = air intake, R2 = pressure